YASKAWA

MOTOMAN MH12, MH12F

Handling & General Applications with the MH-series

The flexible, high speed 6-axis robot MOTOMAN MH12, MH12F with its payload up to 12 kg is newly added to the YASKAWA product line MOTOMAN MH-series. By realising the highest motion performance in its class, YASKAWA is contributing to the productivity development.



The hollow shaft structure is adopted to the upper-arm. By storing the cables in the arm, operation restriction due to the cable interference is reduced. Therefore, maintainability such as simplifying of the robot teaching operation or eliminating of the cable disconnection problems, etc. is improved.

Stream-lined structure adopted to the new type arc welding purpose robot is also applied to this multipurpose-applicable robot. And this adoption contributes to reduce the interference area between the jigs and work pieces. Superior performance can be delivered in handling operations which requires for example the rotation of large-sized work pieces.

The Servo-Float function enables, for example in plastic injection moulding machines, savely handling of work pieces which are pushed back by the ram, including the arm of the robot.


KEY BENEFITS

- Expanded diameter of hollow wrist (50 mm)
- Fast and powerful (max. payload 12 kg)
- · Reduced interference due to internal cable wiring
- Servo float possible
- Stream-lined structure
- · Easy maintenance






MOTOMAN MH12, MH12F



View A




View B



Internal user wiring connector Media connector

View C




Mounting options: Floor, wall, ceiling

All dimensions in mm | Technical data may be subject to change without previous notice | Please request detailed drawings at robotics@yaskawa.eu.com - YR-MA1440/MH12-A00, B-06-2015, A-No. 163283

170° RAMO A x M6, depth 14

Allowable wrist load





Specifications MH12, MH12F Maximum Allowable moment Maximum Allowable **Controlled axes** motion range [°] moment [Nm] of inertia [kg · m²] speed [°/sec.] **Axes** Max. payload [kg] 12 ±170 220 Repeat. pos. accuracy [mm] ± 0.08 +155/-90 200 Max. working range R [mm] 1440 +240/-175 220 Temperature [°C] 0 to +45 +180 410 22 0.65 **Humidity** [%] 20 - 80±135 410 22 0.65 Weight [kg] 130 ±360 610 9.8 0.17 1.5 Power supply, average [KVA]



YASKAWA Europe GmbH · Robotics Division Yaskawastraße 1 · D-85391 Allershausen Tel. +49 (0) 8166/90-0 · Fax +49 (0) 8166/90-103 YASKAWA Europe GmbH · Robotics Division Hauptstraße 185 · D-65760 Eschborn Tel. +49 (0) 6196/77725 - 0 · Fax +49 (0) 6196/77725 - 39